



# CALI VINYL® PRO

BUILDER'S CHOICE WITH MUTE STEP®

*A product line by Cali Bamboo*  
*Distributed by Bamboo-Design.ca*  
**1-844-293-6060**




Aged Hickory Vinyl Builder's Choice

## Where Luxury Looks Meet Commercial Strength

This exclusive luxury vinyl collection delivers the same high standards of any Cali Vinyl floor for a better value. Offered only to builders, designers, and architects, it's the LVP for high-style spaces armed for stampede-level traffic. Made in our most popular colors, this special forces flooring is made for domineering strength, faster installations, and 100% waterproofing. Rugged to the bone, each plank is fortified by GeoCore®, a fortifying backbone of limestone composite for superior structural stability.


### Available Colors




Redefined Pine




Thornwood




Alderwood



Gray Ash



Dusty Dune



Brigantine Pine



Aged Hickory



Blonde Ale



Superior Wear Layer



Waterproof Flooring



Fast Install



Matching Accessories



Easy to Clean



Built to Last



Gray Ash Vinyl Builder's Choice

### Leaner & Meaner

Designed with the large-scale commercial installer in mind, the strongest drop-lock system in the industry is also easier to snap together, meaning flooring can be laid in half the time.

### GeoCore: Bad to the Bone

This backbone of limestone composite resists indentation and delivers 50% better dimensional stability (less expansion and contraction), requiring no acclimation or transition pieces.

### Fear No Moisture

A more muscular construction translates to 100% waterproof flooring over any type of subfloor, and zero acclimation even in kitchens, bathrooms, and sub-grade installations.

### Pros Only

This exclusive line is not available to the public and reserved only for industry professionals who demand the fastest installations and superior, commercial-grade durability.

### Accessories



<b>Grain</b>	HiFi Imaging®
<b>Plank Length</b>	48 inches
<b>Plank Width</b>	7-1/8 inches
<b>Plank Thickness</b>	4.7mm
<b>Wear Layer</b>	0.5mm (20mil)
<b>Attached Pad</b>	1mm IXPE Pad
<b>Sqft./Box</b>	23.77 sqft.
<b>Milling</b>	Click Lock (Rapid Locking System)
<b>Construction</b>	100% Waterproof GeoCore® (SPC Composite)
<b>Installation Method</b>	Floating, Glue Down
<b>Sound Rating (No Drop Ceiling)</b>	<i>With Cali Complete:</i> STC 51 & IIC 54 <i>Without Underlayment:</i> STC 52 & IIC 53
<b>Sound Rating (Drop Ceiling)</b>	<i>With Cali Complete:</i> STC 62 & IIC 66 <i>Without Underlayment:</i> STC 62 & IIC 66
<b>Resin</b>	Low Emitting VOC & Prop 65 Compliant (VOC and Phthalate test results available upon request)
<b>Warranty</b>	50 Year Residential 15 Year Commercial
<b>Fire Rating</b>	1.12 W/cm2 (Class 1)
<b>Radiant Heat Compatible</b>	Yes (up to 85°F)